

Angle Grinder LXT

DGA900ZK



Product Description

36V (18Vx2) LXT • 6 000 min⁻¹ • 230 mm

Efficient brushless tool with brake and safety switch underneath for high-capacity applications

Battery powered Angle Grinder for professionals. Two 18V LXT Li-ion batteries deliver the power and performance for corded demands without leaving the 18V LXT platform. Easy-to-grip, ergonomically designed handle with soft grip provides a sure and comfortable grip. Comes without a battery and a charger. Tool only, battery and charger not included.

Product Features

- Brushless maintenance-free and long-life motor
- Battery protection system automatically shuts off power when the battery level is low

Barcode

88381850407

ъ .		1.61	
Prod	uct Si	pecifica ⁱ	tions

Troduct Specifications		
Bore Size (Arbor Diameter)	22,23 mm	
Max. Depth of Cut	66 mm	
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion	
Grinding Disc Diameter	230 mm	
Vibration Level, Surface Grinding	7,5 m/s ²	
Tool weight with battery (EPTA)	5,2 - 8,0 kg	
Brushless Motor	YES	
Battery Voltage	2 x 18 V	
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²	
Sound Pressure Level	91 dB(A)	
Vibration Level, Disc Sanding	≤ 2,5 m/s²	
Product Dimensions (L x W x H):	499 x 250 x 158 mm	
Spindle Thread	M14	
Sound Power Level (L _{wa})	99 dB(A)	
Voltage LXT	1	
Product net weight (new)	3,4 kg	
System	LXT 18V/36V	
Noise Uncertainty (K Factor)	3 dB(A)	
Tool Category	Grinding, Sanding and Polishing	
Electronic brake	1	
Dead Man's Switch (No Lock-On)	1	
Max Output Power	1500 W	
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²	
Anti-Restart Function (NVR Switch)	1	

No load speed 6000 min⁻¹

Standard Equipment

• With Carry Case and Sold without Battery or Charger

More info

https://makita.ae/product/angle-grinder-lxt-dga900zk/