



Angle Grinder LXT DGA900ZK



Product Description

36V (18Vx2) LXT • 6 000 min⁻¹ • 230 mm

Efficient brushless tool with brake and safety switch underneath for high-capacity applications

Battery powered Angle Grinder for professionals. Two 18V LXT Li-ion batteries deliver the power and performance for corded demands without leaving the 18V LXT platform. Easy-to-grip, ergonomically designed handle with soft grip provides a sure and comfortable grip. Comes without a battery and a charger. Tool only, battery and charger not included.

Product Features

- ◎ Brushless maintenance-free and long-life motor
- ◎ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381850407

Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Max. Depth of Cut	66 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	230 mm
Vibration Level, Surface Grinding	7,5 m/s ²
Tool weight with battery (EPTA)	5,2 - 8,0 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	91 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Product Dimensions (L x W x H):	499 x 250 x 158 mm
Spindle Thread	M14
Sound Power Level (L_{WA})	99 dB(A)
Voltage LXT	1
Product net weight (new)	3,4 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
Max Output Power	1500 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1

No load speed

6000 min⁻¹

Standard Equipment

◎ With Carry Case and Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-lxt-dga900zk/>