

Angle Grinder (X Lock) GA5080R



Product Description

1,400 W • 125 mm • 12,000 min⁻¹ • Anti Restart

First X-Lock Angle Grinder in AC tools range. Efficient tool for Cutting and Grinding.

GA5080R comes with X-LOCK mechanism that enables quick and easy wheel changes and also minimizes over-tightening and loosening of wheels.

Product Specifications

Vibration Level, Surface Grinding	7,9 m/s ²
Max. Depth of Cut	31 mm
Grinding Disc Diameter	125 mm
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	87 dB(A)
Vibration Level, Disc Sanding	4,7 m/s ²
Power Supply Cord	2,5 m
Continuous Input Power	1400 W
Product Dimensions (L x W x H):	309 x 141 x 113 mm
Sound Power Level (L _{WA})	95 dB(A)
Spindle Thread	M14
Weight Without Cable (EPTA)	2,5 - 3,6 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	2100 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1
Tool Category	Grinding, Sanding and Polishing
No load speed	12000 min ⁻¹

More info

<https://makita.ae/product/angle-grinder-x-lock-ga5080r/>