

## Angle Grinder XGT GA038GM204



### Product Description

40V MAX XGT • 230 mm • 6 600 min<sup>-1</sup>

#### Efficient brushless tool for cutting and grinding.

Brushless, paddle switch angle grinder with a 230 mm wheel for demanding professional use. Adjustable speed from 6 600 min<sup>-1</sup> by using variable speed control dial. AWS remote vacuum cleaner start function. Two 5,0 Ah batteries and a charger.

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	22,23 mm
<b>Vibration Level, Surface Grinding</b>	7,5 m/s <sup>2</sup>
<b>Tool weight with battery (EPTA)</b>	4,6 - 8,0 kg
<b>Max. Depth of Cut</b>	73 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Grinding Disc Diameter</b>	230 mm
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Vibration Uncertainty (K Factor), Disc Sanding</b>	1,5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	90 dB(A)
<b>Vibration Level, Disc Sanding</b>	≤ 2,5 m/s <sup>2</sup>
<b>Product Dimensions (L x W x H):</b>	516 x 250 x 176 mm
<b>Sound Power Level (L<sub>WA</sub>)</b>	98 dB(A)
<b>System</b>	XGT 40Vmax/80V max
<b>Spindle Thread</b>	M14
<b>Product net weight (new)</b>	2,9 kg
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max Output Power</b>	1700 W
<b>Vibration Uncertainty (K Factor), Surface Grinding</b>	1,5 m/s <sup>2</sup>
<b>Anti-Restart Function (NVR Switch)</b>	1
<b>Tool Category</b>	Grinding, Sanding and Polishing
<b>Electronic brake</b>	1
<b>Dead Man's Switch (No Lock-On)</b>	1
<b>No load speed</b>	6600 min <sup>-1</sup>
<b>AWS FUNCTION</b>	YES

### Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

More info

<https://makita.ae/product/angle-grinder-xgt-ga038gm204/>