

Angle Grinder XGT GA046GZ



Product Description

40V MAX XGT • 115 mm • 8 500 min⁻¹ • X-lock

Excellent in continuous heavy-duty work

40Vmax XGT BL AFT Cordless 115 mm (5") Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch, X-LOCK

Product Specifications

| | |
|--|---------------------------------|
| Vibration Level, Surface Grinding | 4,0 m/s ² |
| Tool weight with battery (EPTA) | 3,0 - 5,3 kg |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Grinding Disc Diameter | 115 mm |
| Max. Depth of Cut | 26 mm |
| Battery Voltage | 40 V |
| Brushless Motor | YES |
| Vibration Uncertainty (K Factor), Disc Sanding | 1,9 m/s ² |
| Sound Pressure Level | 84 dB(A) |
| Vibration Level, Disc Sanding | ≤ 2,5 m/s ² |
| Product Dimensions (L x W x H): | 418 x 130 x 163 mm |
| Sound Power Level (L _{WA}) | 92 dB(A) |
| System | XGT 40Vmax/80V max |
| Product net weight (new) | 2,0 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max Output Power | 1600 W |
| Vibration Uncertainty (K Factor), Surface Grinding | 1,5 m/s ² |
| Anti-Restart Function (NVR Switch) | 1 |
| Tool Category | Grinding, Sanding and Polishing |
| Electronic brake | 1 |
| Dead Man's Switch (No Lock-On) | 1 |
| No load speed | 8500 min ⁻¹ |

Standard Equipment

⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-xgt-ga046gz/>