

Angle Grinder XGT GA047GZ



Product Description

40V MAX XGT • 125 mm • 8 500 min⁻¹ • X-lock

Excellent in continuous heavy-duty work

40Vmax XGT BL AFT Cordless 125 mm (5") Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch, X-LOCK

Product Specifications

Vibration Level, Surface Grinding	5,0 m/s ²
Tool weight with battery (EPTA)	3,0 - 5,3 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	125 mm
Max. Depth of Cut	31 mm
Battery Voltage	40 V
Brushless Motor	YES
Vibration Uncertainty (K Factor), Disc Sanding	1,9 m/s ²
Sound Pressure Level	84 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Product Dimensions (L x W x H):	418 x 140 x 163 mm
Sound Power Level (L _{WA})	92 dB(A)
System	XGT 40Vmax/80V max
Product net weight (new)	2,1 kg
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	1600 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
No load speed	8500 min ⁻¹

Standard Equipment

⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-xgt-ga047gz/>