

Angle Grinder XGT GA049GT101

Product Description

40V MAX XGT • 115 mm • 11 000 min⁻¹

Model GA049G is a 115 mm (4-1/2") angle grinder powered by 40Vmax XGT® Li-Ion battery

The new housing structure provides high rotation speed similar to that of corded models. Other features and benefits are:

- Slide lever style wheel cover
- Paddle switch



Product Specifications

Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	8,5 m/s ²
Tool weight with battery (EPTA)	3,0 - 5,4 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Grinding Disc Diameter	115 mm
Max. Depth of Cut	29 mm
Battery Voltage	40 V
Brushless Motor	YES
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Sound Pressure Level	85 dB(A)
Vibration Level, Disc Sanding	2,8 m/s ²
Product Dimensions (L x W x H):	410 x 130 x 169 mm
Sound Power Level (L_{WA})	93 dB(A)
System	XGT 40Vmax/80V max
Spindle Thread	M14
Product net weight (new)	1,9 kg
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	2300 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Anti-Restart Function (NVR Switch)	1
Tool Category	Grinding, Sanding and Polishing
Electronic brake	1
Dead Man's Switch (No Lock-On)	1
No load speed	11000 min ⁻¹

Standard Equipment

- ⊙ 1pc DC40RA Fast Charger

⦿ 1pc x BL4050F (5.0Ah) 40V MAX XGT Battery

⦿ Makpac Case

More info

<https://makita.ae/product/angle-grinder-xgt-ga049gt101/>