

Angle Grinder XGT GA049GZ

Product Description

40V MAX XGT • 115 mm • 11 000 min⁻¹

Model GA049G is a 115 mm (4-1/2") angle grinder powered by 40Vmax XGT® Li-Ion battery

The new housing structure provides high rotation speed similar to that of corded models. Other features and benefits are:

- Slide lever style wheel cover
- Paddle switch



Product Specifications

| | |
|---|---------------------------------|
| Bore Size (Arbor Diameter) | 22,23 mm |
| Vibration Level, Surface Grinding | 8,5 m/s ² |
| Tool weight with battery (EPTA) | 3,0 - 5,4 kg |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Grinding Disc Diameter | 115 mm |
| Max. Depth of Cut | 29 mm |
| Battery Voltage | 40 V |
| Brushless Motor | YES |
| Vibration Uncertainty (K Factor), Disc Sanding | 1,5 m/s ² |
| Sound Pressure Level | 85 dB(A) |
| Vibration Level, Disc Sanding | 2,8 m/s ² |
| Product Dimensions (L x W x H): | 410 x 130 x 169 mm |
| Sound Power Level (L_{WA}) | 93 dB(A) |
| System | XGT 40Vmax/80V max |
| Spindle Thread | M14 |
| Product net weight (new) | 1,9 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max Output Power | 2300 W |
| Vibration Uncertainty (K Factor), Surface Grinding | 1,5 m/s ² |
| Anti-Restart Function (NVR Switch) | 1 |
| Tool Category | Grinding, Sanding and Polishing |
| Electronic brake | 1 |
| Dead Man's Switch (No Lock-On) | 1 |
| No load speed | 11000 min ⁻¹ |

Standard Equipment

⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-grinder-xgt-ga049gz/>