

## Angle Impact Driver CXT TL064DZ



### Product Description

12V MAX • 1/4" • 60 Nm • 0 - 2 000 min<sup>-1</sup>

#### Angle impact driver for tight spaces

A compact and light 1/4" angle impact wrench. An angle head height of 53 mm makes this tool an ideal choice for tight spaces. A long paddle switch and handy LED light for added comfort. Tool only, battery and charger not included.

### Product Features

- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ LED light illuminates the work site
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381840538

### Product Specifications

|  |                            |
|--|----------------------------|
| Hex shank                                  | 1/4"                       |
| Tool weight with battery (EPTA)            | 1,2 - 1,6 kg               |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-Ion                     |
| Battery Voltage                            | 12 V                       |
| Vibration Level (3 axes), Fastening Bolt   | 15,0 m/s <sup>2</sup>      |
| Sound Pressure Level                       | 94 dB(A)                   |
| CXT Battery                                | 1                          |
| Capacity machine screw                     | M4 - M8                    |
| Vibration Uncertainty (K Factor)           | 1,5 m/s <sup>2</sup>       |
| Angle length                               | 53 mm                      |
| Tightening Capacity High Tensile Bolt      | M4 - M8                    |
| Product Dimensions (L x W x H):            | 361 x 66 x 86 mm           |
| Product net weight (new)                   | 1,0 kg                     |
| Impacts per Minute (IPM)                   | 0 - 3000 min <sup>-1</sup> |
| System                                     | CXT 12Vmax                 |
| Max Fastening Torque Impact Drill          | 60 Nm                      |
| Sound Power Level (L <sub>WA</sub> )       | 102 dB(A)                  |
| Tightening Capacity Standard Bolt          | M4 - M12                   |
| Noise Uncertainty (K Factor)               | 3 dB(A)                    |
| Tool Category                              | Screwing and Drilling      |
| No load speed                              | 0 - 2000 min <sup>-1</sup> |

### Standard Equipment

- ⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/angle-impact-driver-cxt-tl064dz/>