

# Auto Feed Screwdriver LXT

## DFR550RFE



### Product Description

18V LXT • 25 – 55 mm • 4 000 min<sup>-1</sup>

#### Quick screwdriving with auto-feed system

A cordless 18V LXT screwdriver for screw strips with a speed of 4 000 min<sup>-1</sup> and a robust aluminium auto-feed system for 25 – 55 mm screws. A precise depth control switch and screw guide ensure accuracy and prevent slanted screw feeds. Two 3.0Ah batteries and a rapid charger in a case.

### Product Features

- ⦿ Ergonomically designed handle with rubberized soft grip
- ⦿ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⦿ Compact and lightweight design
- ⦿ Conveniently located forward/reverse switch

### Barcode

88381669474

### Product Specifications

Screwdriving Bit Length	157 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Capacity Drywall Screw	4,0 mm
Tool weight with battery (EPTA)	2,1 - 3,1 kg
Battery Voltage	18 V
Sound Pressure Level	78 dB(A)
Product Dimensions (L x W x H):	424 x 80 x 238 mm
Vibration Level (3 axes)	≤ 2,5 m/s <sup>2</sup>
Voltage LXT	1
Product net weight (new)	1,7 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Driving Shank	0.25 "
Max Output Power	235 W
Tool Category	Screwing and Drilling
No load speed	4000 min <sup>-1</sup>
Collated drywall screw	25#-#55 mm

#### Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ⦿ Carry Case

#### More info

<https://makita.ae/product/auto-feed-screwdriver-lxt-dfr550rfe/>