



## Blower XGT UB001GZ



### Product Description

40V MAX XGT • 64 m/s • 16.0 m<sup>3</sup>/min

**UB001G delivers the high output to tackle more demanding applications with ease.**

A combination of brushless motor and XGT system produce 64m/s of max air velocity, 16.0m<sup>3</sup>/min max air volume and 17Nm blowing force, the user has enough power to tackle any job.

### Product Features

- ◎ Max blowing force can be easily obtained by fully pulling the trigger (Boost mode)
- ◎ High power and less user fatigue
- ◎ Compact and lightweight for single handed operation
- ◎ Lock-on button operable from either side of handle for continuous operation
- ◎ The best choices for use in resorts, public places and residential areas
- ◎ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381740906

### Product Specifications

<b>Tool weight with battery (EPTA)</b>	3,1 - 4,5 kg
<b>Continuous use XGT® 40Vmax / 5.0 Ah</b>	15 / 8 min
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Sound Pressure Level</b>	83,7 dB(A)
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Product Dimensions (L x W x H):</b>	917 - 1017 x 167 x 297 mm
<b>Product net weight (new)</b>	2,4 kg
<b>System</b>	XGT 40Vmax/80V max
<b>Sound Power Level (L<sub>WA</sub>)</b>	94,1 dB(A)
<b>Max. Air Velocity</b>	53 / 64 m/s
<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3,1 dB(A)
<b>Tool Category</b>	Dust Management
<b>Air volume</b>	0 -13,5 / 16 m <sup>3</sup> /min
<b>Blowing force</b>	0 - 17 N
<b>No load speed</b>	0 - 20000 / 23000 min <sup>-1</sup>

## Standard Equipment

◎ Sold without Battery or Charger

## More info

<https://makita.ae/product/blower-xgt-ub001gz/>