

## Circular Saw LXT DHS660Z



### Product Description

18V LXT • 5 000 min<sup>-1</sup> • 165 mm

#### Efficient and compact brushless professional saw with brake

An efficient cordless circular saw with a brake for wood. Accepts blades with 165 mm diameter that achieve a max. cutting depth of 57 mm. Ventilation air is guided through the front to keep the cut line clear and an LED light offers added illumination. Compatible with a guide rule. Tool only, battery and charger not included.

### Product Features

- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ Removable dust extraction connection
- ⊙ Battery level indicator
- ⊙ LED light illuminates the work site
- ⊙ Body model - delivered without battery and charger.
- ⊙ Brushless maintenance-free and long-life motor

### Barcode

88381862912

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	20 mm
<b>Max. Cutting Depth at 45°</b>	41 mm
<b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>	41 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Tool weight with battery (EPTA)</b>	2,9 - 3,2 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	18 V
<b>Max. Cutting Depth at 50°</b>	37 mm
<b>Max. Bevel Range (Left)</b>	0 / 50 °
<b>Sound Pressure Level</b>	93 dB(A)
<b>Product Dimensions (L x W x H):</b>	270 x 186 x 250 mm
<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	104 dB(A)
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	2,5 kg
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)

<b>Vacuum cleaner connection Ø in / out</b>	35/40 mm
<b>Tool Category</b>	Sawing
<b>Max. Cutting Depth at 90°</b>	57 mm
<b>Blade Diameter</b>	165 mm
<b>Max Output Power</b>	680 W
<b>No load speed</b>	5000 min <sup>-1</sup>

#### Standard Equipment

- ⦿ Sold without Battery or Charger

#### More info

<https://makita.ae/product/circular-saw-lxt-dhs660z/>