

Circular Saw XGT HS004GZ01



Product Description

40V MAX XGT • 6 000 min⁻¹ • 190/185 mm

Excellent balance and High power circular saw with AWS function

Lightweight & High Power. BL motor delivers 6,000 RPM for fast cutting. Automatic torque Drive Technology (ADT) adjusts cutting speed and torque during cut for optimum performance. Blinks green to indicate that the tool is overloaded ADT indicator lamp. Compatible with guide rail without adapter. Tool only, battery and charger not included.

Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Auto-start Wireless System (AWS) connects to vacuum cleaner with Bluetooth
- ⊙ Compatible with guide rail without adapter
- ⊙ Electric brake for maximum productivity and increased operator safety
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⊙ Magnesium components create lightweight saws that are well-balanced and jobsite tough
- ⊙ Twin LED lights with preglow and afterglow functions for better illumination and more accurate work

Barcode

88381720038

Product Specifications

| | |
|---|------------------------|
| Bore Size (Arbor Diameter) | 20 / 30 mm |
| Tool weight with battery (EPTA) | 4,4 - 5,6 kg |
| Max. Cutting Depth at 45° | 44,5 mm |
| Capacity 45° (Miter R/L 45°, Bevel 0°) | 44,5 / 43,0 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Battery Voltage | 40 V |
| Brushless Motor | YES |
| Sound Pressure Level | 93 dB(A) |
| Max. Bevel Range (Left) | 0 / 48 ° |
| Product Dimensions (L x W x H): | 337 x 210 x 290 mm |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| System | XGT 40Vmax/80V max |
| Vibration Level (3 axes) | ≤ 2,5 m/s ² |
| Sound Power Level (L_{WA}) | 104 dB(A) |

| | |
|---|------------------------|
| Product net weight (new) | 3,7 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vacuum cleaner connection Ø in / out | 35/40 mm |
| Max. Cutting Depth at 90° | 62,5 mm |
| Blade Diameter | 185 / 190 mm |
| Max Output Power | 1300 W |
| Max. Cutting Depth at 48° | 42 / 41 mm |
| Tool Category | Sawing |
| AWS FUNCTION | YES |
| No load speed | 6000 min ⁻¹ |

Standard Equipment

- ⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/circular-saw-xgt-hs004gz01/>