

Combination Hammer

HR2630T



Product Description

800 W • SDS-Plus • 26 mm • 2,9 J

Three-mode rotary hammer with quick-change chuck

A compact and efficient combination hammer compatible with SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min⁻¹ from a switch. Impact energy of 2,9 J and optimal drilling range of 8 - 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.

Product Features

- ◎ The rubber coating on the handle ensures a firm working grip
- ◎ Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- ◎ 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- ◎ Variable speed trigger allows the user to adjust discharge rate
- ◎ Depth gauge for increased drilling consistency

Barcode

88381687393

Product Specifications

Power Supply Cord UK	2,5 m
Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Drilling diameter with TCT core bit	68 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	14,5 m/s ²
Optimum Drilling Diameter Range in Concrete	8.0-18 mm
Sound Pressure Level	90 dB(A)
Power Supply Cord	4,0 m
Impact Energy	2,4 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	10,9 m/s ²
Product Dimensions (L x W x H):	385 x 77 x 209 mm
Impacts per Minute (IPM)	0 - 4600 min ⁻¹
Sound Power Level (L_{WA})	101 dB(A)
Weight Without Cable (EPTA)	3,0 kg

Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	26 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
No load speed	0 - 1200 min ⁻¹

More info

<https://makita.ae/product/combination-hammer-hr2630t/>