

## Combination Hammer

# HR2631F



### Product Description

800 W • SDS-Plus • 26 mm • 2,9 J

#### Professional three-mode, anti-vibration rotary hammer

An efficient combination hammer with AVT anti-vibration system for SDS-Plus bits. Suitable for impact and unstressed drilling and chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min<sup>-1</sup> from a switch. Impact energy of 2,9 J and optimal drilling range of 8 - 18 mm in concrete, with a max. capacity of 26 mm.

### Product Features

- ⊙ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ LED light illuminates the work site

### Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s <sup>2</sup>
Drilling diameter with TCT core bit	68 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	12,4 m/s <sup>2</sup>
Optimum Drilling Diameter Range in Concrete	8.0-18 mm
Sound Pressure Level	92 dB(A)
Power Supply Cord	2,5 m
Impact Energy	2,4 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Vibration: Chiselling	9,2 m/s <sup>2</sup>
Product Dimensions (L x W x H):	385 x 77 x 209 mm
Impacts per Minute (IPM)	0 - 4600 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	103 dB(A)
Weight Without Cable (EPTA)	2,9 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	26 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
No load speed	0 - 1200 min <sup>-1</sup>

More info

<https://makita.ae/product/combination-hammer-hr2631f/>