

Combination Hammer

HR2810



Product Description

800 W • SDS-Plus • 28 mm • 2,9 J

Professional three-mode rotary hammer

An efficient combination hammer for SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. 800 W output and speed can be adjusted between 0 and 1 100 min⁻¹ from a switch. Impact energy of 2,8 J and optimal drilling range of 8 – 20 mm in concrete. Max. drilling capacity of 28 mm in concrete.

Product Features

- ⦿ Torque Limiting Clutch Engineered to Prevent Gear Damage
- ⦿ Recessed lock-on button for continuous operation
- ⦿ Depth gauge for increased drilling consistency
- ⦿ Torque limiting clutch engineered to minimize gear damage by automatically disengaging gears if the bit binds
- ⦿ Lock-on button for user convenience during longer work periods
- ⦿ Double insulated

Barcode

88381083829

Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Drilling diameter with TCT core bit	80 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	19,9 m/s ²
Optimum Drilling Diameter Range in Concrete	8.0-20 mm
Sound Pressure Level	89 dB(A)
Power Supply Cord	2,5 m
Impact Energy	2,8 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,7 m/s ²
Vibration: Chiselling	17,1 m/s ²
Product Dimensions (L x W x H):	314 x 89 x 225 mm
Impacts per Minute (IPM)	0 - 4500 min ⁻¹
Sound Power Level (L _{WA})	100 dB(A)
Weight Without Cable (EPTA)	3,8 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	28 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling

No load speed	0 - 1100 min ⁻¹
---------------	----------------------------

More info

<https://makita.ae/product/combination-hammer-hr2810/>