

Combination Hammer

HR3210C



Product Description

850 W • SDS-Plus • 32 mm • 5,5 J

High performance Combination Hammer for SDS-Plus drill bits

High performance combination Hammer for SDS-Plus with 850 W motor. Three functions: impact drill, no impact and demolition mode. Drilling power for concrete 32mm.

Product Features

- The rubber coating on the handle ensures a firm working grip
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance

Barcode

88381088718

| Product Specifications | |
|---|-------------------------------|
| Vibration Level (3 axes), Drilling | ≤ 2,5 m/s ² |
| Drilling diameter with TCT core bit | 90 mm |
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 32 mm |
| Vibration Level (3 axes), Impact Drilling | 9,2 m/s ² |
| Optimum Drilling Diameter Range in Concrete | 10.0-22 mm |
| Sound Pressure Level | 89 dB(A) |
| Power Supply Cord | 5,0 m |
| Impact Energy | 5,0 J |
| Continuous Input Power | 850 W |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Vibration: Chiselling | 7,5 m/s ² |
| Product Dimensions (L x W x H): | 398 x 114 x 239 mm |
| Impacts per Minute (IPM) | 1650 - 3300 min ⁻¹ |
| Sound Power Level (L _{wA}) | 100 dB(A) |
| Weight Without Cable (EPTA) | 4,8 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 32 mm |
| Adapted for SDS-PLUS bits | 1 |
| Tool Category | Hammer Drilling and Chiseling |
| No load speed | 315 - 630 min ⁻¹ |

More info