

## Combination Hammer LXT DHR202RFJ



### Product Description

18V LXT • SDS-PLUS • 20 mm • 1,9 J

#### Professional three-mode combination hammer

An efficient combination hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 - 1 100 min<sup>-1</sup>. Impact energy of 1,9 J and max. drilling capacity of 20 mm in concrete. Includes 2 x 3,0 Ah batteries and a charger in a Makpac case.

### Product Features

- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ LED light illuminates the work site
- ⊙ Impact drilling, non-impact drilling and spike function
- ⊙ Reversing switch
- ⊙ Compact and ergonomic design
- ⊙ Works with 18V Li-ion battery (not 1.3Ah battery)
- ⊙ Easy blade setting system for fast blade installation
- ⊙ 40-fold chisel adjustment

### Barcode

88381658164

### Product Specifications

<b>Vibration Level (3 axes), Drilling</b>	3 m/s <sup>2</sup>
<b>Max. Drilling Diameter in Steel</b>	13 mm
<b>Max. Drilling Diameter in Wood</b>	26 mm
<b>Optimum Drilling Diameter Range in Concrete</b>	6,0-10 mm
<b>Vibration Level (3 axes), Impact Drilling</b>	15,1 m/s <sup>2</sup>
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Drilling diameter with TCT core bit</b>	54 mm
<b>Tool weight with battery (EPTA)</b>	3,2 - 4,0 kg
<b>Battery Voltage</b>	18 V
<b>Sound Pressure Level</b>	88 dB(A)
<b>Product Dimensions (L x W x H):</b>	358 x 84 x 259 mm
<b>Vibration: Chiselling</b>	14,1 m/s <sup>2</sup>
<b>Impacts per Minute (IPM)</b>	0 - 4000 min <sup>-1</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	99 dB(A)
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	2,6 kg
<b>Impact Energy</b>	1,9 J
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>

<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Hammer Drilling and Chiseling
<b>Adapted for SDS-PLUS bits</b>	1
<b>Electronic brake</b>	1
<b>Max. Drilling Diameter in Concrete</b>	20 mm
<b>Max. Drilling Diameter in Masonry</b>	20 mm
<b>Max Output Power</b>	330 W
<b>No load speed</b>	0 - 1100 min <sup>-1</sup>

#### Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ⦿ Makpac Case

#### More info

<https://makita.ae/product/combination-hammer-lxt-dhr202rfj/>