

Combination Hammer LXT

DHR242RFJ



Product Description

18V LXT • SDS-PLUS • 24 mm • 2,0 J

Professional brushless, three-mode combination hammer

An efficient combination hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 - 950 min⁻¹. Impact energy of 2,0 J and max. drilling capacity of 24 mm in concrete. Includes 2 x 3,0 Ah batteries and a charger in a Makpac case.

Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381654418

Product Specifications

| | |
|---|-------------------------------|
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 27 mm |
| Optimum Drilling Diameter Range in Concrete | 6,0-12 mm |
| Vibration Level (3 axes), Impact Drilling | 15,0 m/s ² |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Drilling diameter with TCT core bit | 54 mm |
| Tool weight with battery (EPTA) | 3,4 - 3,8 kg |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Sound Pressure Level | 90 dB(A) |
| Product Dimensions (L x W x H): | 328 x 85 x 213 mm |
| Vibration: Chiselling | 11,4 m/s ² |
| Impacts per Minute (IPM) | 0 - 4700 min ⁻¹ |
| Sound Power Level (L _{WA}) | 101 dB(A) |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 3,1 kg |
| Impact Energy | 2,0 J |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Tool Category | Hammer Drilling and Chiseling |
| Adapted for SDS-PLUS bits | 1 |
| Electronic brake | 1 |
| Max. Drilling Diameter in Concrete | 24 mm |

No load speed

0 - 950 min⁻¹

Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ⦿ Makpac Case

More info

<https://makita.ae/product/combination-hammer-lxt-dhr242rfj/>