

## Combination Hammer LXT DHR242RTJ



### Product Description

18V LXT • SDS-PLUS • 24 mm • 2,0 J

#### Professional brushless, three-mode combination hammer

An efficient combination hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 - 950 min<sup>-1</sup>. Impact energy of 2,0 J and max. drilling capacity of 24 mm in concrete. Includes 2 x 5,0 Ah batteries and a charger in a Makpac case.

### Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381677059

### Product Specifications

|   |                               |
|---|-------------------------------|
| Max. Drilling Diameter in Steel             | 13 mm                         |
| Max. Drilling Diameter in Wood              | 27 mm                         |
| Optimum Drilling Diameter Range in Concrete | 6,0-12 mm                     |
| Vibration Level (3 axes), Impact Drilling   | 15,0 m/s <sup>2</sup>         |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)  | Li-ion                        |
| Drilling diameter with TCT core bit         | 54 mm                         |
| Tool weight with battery (EPTA)             | 3,4 - 3,8 kg                  |
| Brushless Motor                             | YES                           |
| Battery Voltage                             | 18 V                          |
| Sound Pressure Level                        | 90 dB(A)                      |
| Product Dimensions (L x W x H):             | 328 x 85 x 213 mm             |
| Vibration: Chiselling                       | 11,4 m/s <sup>2</sup>         |
| Impacts per Minute (IPM)                    | 0 - 4700 min <sup>-1</sup>    |
| Sound Power Level (L <sub>WA</sub> )        | 101 dB(A)                     |
| Voltage LXT                                 | 1                             |
| System                                      | LXT 18V/36V                   |
| Product net weight (new)                    | 3,1 kg                        |
| Impact Energy                               | 2,0 J                         |
| Vibration Uncertainty (K Factor)            | 1,5 m/s <sup>2</sup>          |
| Noise Uncertainty (K Factor)                | 3 dB(A)                       |
| Tool Category                               | Hammer Drilling and Chiseling |
| Adapted for SDS-PLUS bits                   | 1                             |
| Electronic brake                            | 1                             |
| Max. Drilling Diameter in Concrete          | 24 mm                         |

**No load speed**

0 - 950 min<sup>-1</sup>

### Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⊙ Makpac Case

### More info

<https://makita.ae/product/combination-hammer-lxt-dhr242rtj/>