

Combination Hammer LXT DHR242RTJ



Product Description

18V LXT • SDS-PLUS • 24 mm • 2,0 J

Professional brushless, three-mode combination hammer

An efficient combination hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 - 950 min⁻¹. Impact energy of 2,0 J and max. drilling capacity of 24 mm in concrete. Includes 2 x 5,0 Ah batteries and a charger in a Makpac case.

Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381677059

Product Specifications

Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	27 mm
Optimum Drilling Diameter Range in Concrete	6,0-12 mm
Vibration Level (3 axes), Impact Drilling	15,0 m/s ²
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Drilling diameter with TCT core bit	54 mm
Tool weight with battery (EPTA)	3,4 - 3,8 kg
Brushless Motor	YES
Battery Voltage	18 V
Sound Pressure Level	90 dB(A)
Product Dimensions (L x W x H):	328 x 85 x 213 mm
Vibration: Chiselling	11,4 m/s ²
Impacts per Minute (IPM)	0 - 4700 min ⁻¹
Sound Power Level (L _{WA})	101 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	3,1 kg
Impact Energy	2,0 J
Vibration Uncertainty (K Factor)	1,5 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Hammer Drilling and Chiseling
Adapted for SDS-PLUS bits	1
Electronic brake	1
Max. Drilling Diameter in Concrete	24 mm

No load speed

0 - 950 min⁻¹

Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⊙ Makpac Case

More info

<https://makita.ae/product/combination-hammer-lxt-dhr242rtj/>