

Combination Hammer LXT

DHR242Z



Product Description

18V LXT • SDS-PLUS • 24 mm • 2,0 J

Professional brushless, three-mode combination hammer An efficient combination hammer for SDS-Plus bits with an antivibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min-1. Impact energy of 2,0 J and max. drilling capacity of 24 mm in concrete. Tool only, battery and charger not included.

Product Features

- Brushless maintenance-free and long-life motor
- Body model delivered without battery and charger.
- Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381654326

D		100	
Proc	luct Sp	естпса	ations

1 Todact Specifications		
Max. Drilling Diameter in Steel	13 mm	
Max. Drilling Diameter in Wood	27 mm	
Vibration Level (3 axes), Impact Drilling	15,0 m/s ²	
Optimum Drilling Diameter Range in Concrete	6,0-12 mm	
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion	
Drilling diameter with TCT core bit	54 mm	
Tool weight with battery (EPTA)	3,4 - 3,8 kg	
Brushless Motor	YES	
Battery Voltage	18 V	
Sound Pressure Level	90 dB(A)	
Product Dimensions (L x W x H):	328 x 85 x 213 mm	
Vibration: Chiselling	11,4 m/s ²	
Impacts per Minute (IPM)	0 - 4700 min ⁻¹	
Sound Power Level (L _{WA})	101 dB(A)	
Voltage LXT	1	
System	LXT 18V/36V	
Product net weight (new)	3,1 kg	
Impact Energy	2,0 J	
Vibration Uncertainty (K Factor)	1,5 m/s ²	
Noise Uncertainty (K Factor)	3 dB(A)	
Tool Category	Hammer Drilling and Chiseling	
Adapted for SDS-PLUS bits	1	
Electronic brake	1	
Max. Drilling Diameter in Concrete	24 mm	

No load speed 0 - 950 min⁻¹

Standard Equipment

Sold without Battery or Charger

More info

https://makita.ae/product/combination-hammer-lxt-dhr242z/