

Combination Hammer LXT

DHR281PT2J



Product Description

36V (18Vx2) LXT • SDS-PLUS • 28 mm • 3,2 J

Brushless, three-mode, anti-vibration combination hammer with quick change chuck for professionals

A robust tool for SDS-Plus bits with AVT (anti-vibration technology) and a quick change chuck. Suited to impact and unstressed drilling and chipping. Speed range of $0-980\ min-1$. Impact energy of 3,2 J max. drilling capacity of 28 mm in concrete. Includes $2\times5,0\ Ah$ batteries and a two port charger in a Makpac case.

Product Features

- Brushless maintenance-free and long-life motor
- LED light illuminates the work site
- Body model delivered without battery and charger.
- Body model delivered without battery and charger.
- Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381858038

Product Specifications	
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	13,3 m/s ²
Optimum Drilling Diameter Range in Concrete	10,0-18 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Drilling diameter with TCT core bit	54 mm
Tool weight with battery (EPTA)	4,0 - 4,9 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Sound Pressure Level	93 dB(A)
Product Dimensions (L x W x H):	404 x 134 x 232 mm
Vibration: Chiselling	9,3 m/s ²
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
Sound Power Level (L _{WA})	104 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	3,1 kg
Impact Energy	2,9 J
Vibration Uncertainty (K Factor)	2,4 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Hammer Drilling and Chiseling

Adapted for SDS-PLUS bits	1
Electronic brake	1
Max. Drilling Diameter in Concrete	28 mm
No load speed	0 - 980 min ⁻¹

Standard Equipment

- ② 2pcs BL1850B (5.0Ah) 18V LXT Battery
- Makpac Case

More info

https://makita.ae/product/combination-hammer-lxt-dhr281pt2j/