

## Combination Hammer LXT

# DHR283ZJ



### Product Description

36V (18Vx2) LXT • SDS-PLUS • 28 mm • 3,2 J

**Brushless, three-mode, anti-vibration combination hammer with quick change chuck for professionals and with AWS function**

An efficient tool with AVT (anti-vibration technology), remote dust extraction start and a quick change chuck, accepts SDS-Plus bits. Two 18V LXT batteries provide a high voltage of 18V+18V. For impact and unstressed drilling and chipping. Impact energy of 3,2 J, max. capacity of 28 mm in concrete. Tool in Makpac case, battery and charger not included.

### Product Features

- ◉ Brushless maintenance-free and long-life motor
- ◉ LED light illuminates the work site
- ◉ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381857888

### Product Specifications

Plastic Carrying Case	1
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	13,3 m/s <sup>2</sup>
Optimum Drilling Diameter Range in Concrete	10,0-18 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Drilling diameter with TCT core bit	54 mm
Tool weight with battery (EPTA)	4,0 - 4,9 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Sound Pressure Level	93 dB(A)
Product Dimensions (L x W x H):	404 x 134 x 232 mm
Vibration: Chiselling	9,3 m/s <sup>2</sup>
Impacts per Minute (IPM)	0 - 5000 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	104 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	3,1 kg
Impact Energy	2,9 J
Vibration Uncertainty (K Factor)	2,4 m/s <sup>2</sup>
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Hammer Drilling and Chiseling

<b>Adapted for SDS-PLUS bits</b>	1
<b>Electronic brake</b>	1
<b>Max. Drilling Diameter in Concrete</b>	28 mm
<b>No load speed</b>	0 - 980 min <sup>-1</sup>
<b>AWS FUNCTION</b>	YES

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/combination-hammer-lxt-dhr283zj/>