

Combination Hammer XGT

HR002GM201



Product Description

40V MAX XGT • SDS-PLUS • 28 mm • 3,2 J

Three-mode, anti-vibration combination hammer with remote dust extraction start for professionals

Efficient combination hammer HR002G delivers high power for professional work. The tool is lightweight and the tool balance is redesigned for increased operability. HR002G is equipped with Anti vibration technology (AVT), Active Feedback Technology (AFT) and Auto-start Wireless System (AWS). Two 4.0 Ah batteries, rapid charger and wireless unit in a Makpac case.

Product Features

- ⊙ Quick-release chuck for metal and wood drill bits without impact.
- ⊙ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ⊙ Auto-start Wireless System (AWS) connects to vacuum cleaner with Bluetooth
- ⊙ Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Low power consumption thanks to brushless motor
- ⊙ Impact drilling, non-impact drilling and spike function
- ⊙ Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381892841

Product Specifications

Vibration Level (3 axes), Drilling	2,5 m/s ²
Drilling diameter with TCT core bit	54 mm
Tool weight with battery (EPTA)	4,1 - 5,5 kg
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes), Impact Drilling	15,6 m/s ²
Optimum Drilling Diameter Range in Concrete	10.0-18 mm
Battery Voltage	40 V
Brushless Motor	YES
Sound Pressure Level	93 dB(A)
Impact Energy	2,9 J
Vibration Uncertainty (K Factor)	2,4 m/s ²
Vibration: Chiselling	11,4 m/s ²

Product Dimensions (L x W x H):	404 x 102 x 238 mm
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
System	XGT 40Vmax/80V max
Sound Power Level (L_{WA})	104 dB(A)
Product net weight (new)	3,1 kg
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	28 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
Electronic brake	1
AWS FUNCTION	YES
No load speed	0 - 980 min ⁻¹

Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

More info

<https://makita.ae/product/combination-hammer-xgt-hr002gm201/>