

# Combination Hammer XGT

## HR003GM201



### Product Description

40V MAX XGT • SDS-PLUS • 28 mm • 3,2 J

#### Powerful three-action hammer with vibration damping

Efficient combination hammer delivers high power for professional work. The tool is lightweight and the tool balance is redesigned for increased operability. Equipped with Anti vibration technology (AVT). Two 4.0 Ah batteries, rapid charger, and dust extraction system in a Makpac case.

### Product Features

- ⦿ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ⦿ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⦿ Low power consumption thanks to brushless motor
- ⦿ Impact drilling, non-impact drilling and spike function
- ⦿ Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- ⦿ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381892995

### Product Specifications

|   |                            |
|---|----------------------------|
| Vibration Level (3 axes), Drilling          | 2,5 m/s <sup>2</sup>       |
| Drilling diameter with TCT core bit         | 54 mm                      |
| Tool weight with battery (EPTA)             | 3,9 - 5,5 kg               |
| Max. Drilling Diameter in Steel             | 13 mm                      |
| Max. Drilling Diameter in Wood              | 32 mm                      |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)  | Li-ion                     |
| Vibration Level (3 axes), Impact Drilling   | 15,0 m/s <sup>2</sup>      |
| Optimum Drilling Diameter Range in Concrete | 10.0-18 mm                 |
| Battery Voltage                             | 40 V                       |
| Brushless Motor                             | YES                        |
| Sound Pressure Level                        | 92 dB(A)                   |
| Impact Energy                               | 2,8 J                      |
| Vibration Uncertainty (K Factor)            | 2,5 m/s <sup>2</sup>       |
| Vibration: Chiselling                       | 11,2 m/s <sup>2</sup>      |
| Product Dimensions (L x W x H):             | 358 x 102 x 238 mm         |
| Impacts per Minute (IPM)                    | 0 - 5000 min <sup>-1</sup> |
| System                                      | XGT 40Vmax/80V max         |
| Sound Power Level (L <sub>WA</sub> )        | 103 dB(A)                  |

|                                    |                               |
|------------------------------------|-------------------------------|
| Product net weight (new)           | 3,1 kg                        |
| Voltage XGT                        | 1                             |
| Noise Uncertainty (K Factor)       | 3 dB(A)                       |
| Max. Drilling Diameter in Concrete | 28 mm                         |
| Adapted for SDS-PLUS bits          | 1                             |
| Tool Category                      | Hammer Drilling and Chiseling |
| Electronic brake                   | 1                             |
| No load speed                      | 0 - 980 min <sup>-1</sup>     |

Standard Equipment

- ⦿ 1pc DC40RA Fast Charger
- ⦿ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⦿ Makpack Case

More info

<https://makita.ae/product/combination-hammer-xgt-hr003gm201/>