

Combination Hammer XGT HR007GM201



Product Description

40V MAX XGT • SDS-PLUS • 54 mm • 3,0 J

Three-mode, anti-vibration rotary hammer for professionals
HR007G has 3-mode operation; “rotation only”, “hammering with rotation” and “hammering only”. LED light illuminates drilling surface for more productivity in low light applications. It is also equipped with Auto-start Wireless System (AWS) and Anti-Vibration Technology (AVT).

Product Features

- ⊙ Soft grip handle provides increased comfort on the job
- ⊙ Impact drilling, non-impact drilling and spike function
- ⊙ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Low power consumption thanks to brushless motor
- ⊙ Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Active Feedback sensing Technology (AFT) turns the motor off if bit rotation is suddenly forced to stop
- ⊙ eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- ⊙ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth

Barcode

88381754798

Product Specifications

| | |
|--|-----------------------|
| Vibration Level (3 axes), Drilling | 2,5 m/s ² |
| Drilling diameter with TCT core bit | 54 mm |
| Tool weight with battery (EPTA) | 3,8 - 5,4 kg |
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 32 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Impact Drilling | 10,4 m/s ² |
| Optimum Drilling Diameter Range in Concrete | 10.0-18 mm |
| Battery Voltage | 40 V |
| Brushless Motor | YES |
| Sound Pressure Level | 91 dB(A) |
| Impact Energy | 3,0 J |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |

| | |
|---|-------------------------------|
| Vibration: Chiselling | 9,7 m/s ² |
| Product Dimensions (L x W x H): | 473 x 101 x 240 mm |
| Impacts per Minute (IPM) | 0 - 5000 min ⁻¹ |
| System | XGT 40Vmax/80V max |
| Sound Power Level (L_{WA}) | 102 dB(A) |
| Product net weight (new) | 2,9 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 28 mm |
| Adapted for SDS-PLUS bits | 1 |
| Tool Category | Hammer Drilling and Chiseling |
| Electronic brake | 1 |
| AWS FUNCTION | YES |
| No load speed | 0 - 980 min ⁻¹ |

Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

More info

<https://makita.ae/product/combination-hammer-xgt-hr007gm201/>