

# Combination Hammer XGT

## HR008GM201

### Product Description

40V MAX XGT • SDS-PLUS • 30 mm • 3,9 J

**Three-mode, anti-vibration rotary hammer with remote dust extraction start for professionals**

HR008G is a XGT Battery Powered powerful Combination Hammer with low vibration due to 2 Counterweights, Anti-vibration rear handle and Anti-vibration side grip yet maintaining high power.



### Product Features

- ⊙ Soft grip handle provides increased comfort on the job
- ⊙ Impact drilling, non-impact drilling and spike function
- ⊙ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Low power consumption thanks to brushless motor
- ⊙ Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Active Feedback sensing Technology (AFT) turns the motor off if bit rotation is suddenly forced to stop
- ⊙ eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- ⊙ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth

### Barcode

88381764643

### Product Specifications

<b>Vibration Level (3 axes), Drilling</b>	5,1 m/s <sup>2</sup>
<b>Drilling diameter with TCT core bit</b>	80 mm
<b>Tool weight with battery (EPTA)</b>	5,2 - 6,8 kg
<b>Max. Drilling Diameter in Steel</b>	13 mm
<b>Max. Drilling Diameter in Wood</b>	32 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Vibration Level (3 axes), Impact Drilling</b>	11,8 m/s <sup>2</sup>
<b>Optimum Drilling Diameter Range in Concrete</b>	30-80 mm
<b>Battery Voltage</b>	40 V

<b>Brushless Motor</b>	YES
<b>Sound Pressure Level</b>	92 dB(A)
<b>Impact Energy</b>	3,9 J
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Vibration: Chiselling</b>	8,6 m/s <sup>2</sup>
<b>Product Dimensions (L x W x H):</b>	422 x 97 x 242 mm
<b>Impacts per Minute (IPM)</b>	0 - 4500 min <sup>-1</sup>
<b>System</b>	XGT 40Vmax/80V max
<b>Sound Power Level (L<sub>WA</sub>)</b>	103 dB(A)
<b>Product net weight (new)</b>	4,3 kg
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Drilling Diameter in Concrete</b>	30 mm
<b>Adapted for SDS-PLUS bits</b>	1
<b>Tool Category</b>	Hammer Drilling and Chiseling
<b>Electronic brake</b>	1
<b>AWS FUNCTION</b>	YES
<b>No load speed</b>	0 - 840 min <sup>-1</sup>

#### Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

#### More info

<https://makita.ae/product/combination-hammer-xgt-hr008gm201/>