



Combination Hammer XGT

HR008GM201



Product Description

40V MAX XGT • SDS-PLUS • 30 mm • 3,9 J

Three-mode, anti-vibration rotary hammer with remote dust extraction start for professionals

HR008G is a XGT Battery Powered powerful Combination Hammer with low vibration due to 2 Counterweights, Anti-vibration rear handle and Anti-vibration side grip yet maintaining high power.

Product Features

- ◎ Soft grip handle provides increased comfort on the job
- ◎ Impact drilling, non-impact drilling and spike function
- ◎ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ◎ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ◎ Low power consumption thanks to brushless motor
- ◎ Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- ◎ Battery protection circuit protects against overloading, over-discharging and over-heating
- ◎ Brushless maintenance-free and long-life motor
- ◎ Active Feedback sensing Technology (AFT) turns the motor off if bit rotation is suddenly forced to stop
- ◎ eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- ◎ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth

Barcode

88381764643

Product Specifications

Vibration Level (3 axes), Drilling	5,1 m/s ²
Drilling diameter with TCT core bit	80 mm
Tool weight with battery (EPTA)	5,2 - 6,8 kg
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes), Impact Drilling	11,8 m/s ²
Optimum Drilling Diameter Range in Concrete	30-80 mm
Battery Voltage	40 V

Brushless Motor	YES
Sound Pressure Level	92 dB(A)
Impact Energy	3,9 J
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	8,6 m/s ²
Product Dimensions (L x W x H):	422 x 97 x 242 mm
Impacts per Minute (IPM)	0 - 4500 min ⁻¹
System	XGT 40Vmax/80V max
Sound Power Level (L_{WA})	103 dB(A)
Product net weight (new)	4,3 kg
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	30 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
Electronic brake	1
AWS FUNCTION	YES
No load speed	0 - 840 min ⁻¹

Standard Equipment

- ◎ 1pc DC40RA Fast Charger
- ◎ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ◎ Makpack Case

More info

<https://makita.ae/product/combination-hammer-xgt-hr008gm201/>