

Combination Hammer XGT

HR010GZ

Product Description

40V MAX XGT • SDS-PLUS • 20 mm • 2,0 J

Efficient, lightweight and compact cordless combination hammer

Efficient and lightweight XGT powered tool with SDS-PLUS shank. New compact DX16 dust collection system further improves usability. Equipped with anti-vibration handle structure and anti-vibration side grips reducing the load on the user. Battery and charger are sold separately.



Product Features

- ⦿ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⦿ Built-in LED light illuminates the work area
- ⦿ Extreme Protection Technology (XPT) engineered to provide increased dust and water resistance in harsh job site conditions
- ⦿ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth

Barcode

88381782128

Product Specifications

| | |
|--|----------------------------|
| Drilling diameter with TCT core bit | 35 mm |
| Tool weight with battery (EPTA) | 2,8 - 4,5 kg |
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 26 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Impact Drilling | 10,0 m/s ² |
| Battery Voltage | 40 V |
| Brushless Motor | YES |
| Impact Energy | 2,1 J |
| Vibration Uncertainty (K Factor) | 1,7 m/s ² |
| Vibration: Chiselling | 7,6 m/s ² |
| Product Dimensions (L x W x H): | 304 x 93 x 223 mm |
| Impacts per Minute (IPM) | 0 - 5000 min ⁻¹ |
| System | XGT 40Vmax/80V max |
| Product net weight (new) | 2,1 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 20 mm |
| Adapted for SDS-PLUS bits | 1 |

| | |
|------------------|-------------------------------|
| Tool Category | Hammer Drilling and Chiseling |
| Electronic brake | 1 |
| AWS FUNCTION | YES |
| No load speed | 0 - 1350 min ⁻¹ |

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/combination-hammer-xgt-hr010gz/>