

Concrete Vibrator XGT

VR001G



Product Description

40V MAX XGT

XGT® **Battery powered Concrete Vibrator for professionals**The combination of XGT battery and Brushless Motor of the machine delivers more run time with maximum vibrations per minute for strengthening concrete in a wide variety of applications such as floors, columns, walls, piers and stairs.

- Two power mode selection (normal/power) allows to use the machine for a wide range of jobsites:-
- Power mode: For a wide range of concrete compaction, such as of soil floors, pillars, and mat foundations
- Normal mode: Ideal for delicate works, such as step finishing or closure of temporary construction openings, where concrete is required not to flow out of the mold
- Constant speed control allows for stable compaction work
- Lock-on switch reduces hand fatigue in long continuous operation
- Compact and ergonomic design and weight only 1.4kg (without battery) for reduced operator fatigue

Product Specifications	
Tool weight with battery (EPTA)	4,8 - 7,8 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	40 V
Vibrator Shaft Diameter	32 - 38 mm
Brushless Motor	YES
Sound Pressure Level	80 dB(A)
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product Dimensions (L x W x H):	282 x 112 x 258 mm
Product net weight (new)	1,4 kg
System	XGT 40Vmax/80V max
Vibration Level (3 axes)	4,9 m/s²
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Stirring and Compressing
Vibrations per minute	12 000 - 15 500 min ⁻¹

More info

https://makita.ae/product/concrete-vibrator-xgt-vr001g/