

## Concrete Vibrator XGT VR001G



### Product Description

40V MAX XGT

#### **XGT® Battery powered Concrete Vibrator for professionals**

The combination of XGT battery and Brushless Motor of the machine delivers more run time with maximum vibrations per minute for strengthening concrete in a wide variety of applications such as floors, columns, walls, piers and stairs.

- Two power mode selection (normal/power) allows to use the machine for a wide range of jobsites:-
  - Power mode: For a wide range of concrete compaction, such as of soil floors, pillars, and mat foundations
  - Normal mode: Ideal for delicate works, such as step finishing or closure of temporary construction openings, where concrete is required not to flow out of the mold
- Constant speed control allows for stable compaction work
- Lock-on switch reduces hand fatigue in long continuous operation
- Compact and ergonomic design and weight only 1.4kg (without battery) for reduced operator fatigue

### Product Specifications

|   |                                   |
|---|-----------------------------------|
| <b>Tool weight with battery (EPTA)</b>            | 4,8 - 7,8 kg                      |
| <b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b> | Li-ion                            |
| <b>Battery Voltage</b>                            | 40 V                              |
| <b>Vibrator Shaft Diameter</b>                    | 32 - 38 mm                        |
| <b>Brushless Motor</b>                            | YES                               |
| <b>Sound Pressure Level</b>                       | 80 dB(A)                          |
| <b>Vibration Uncertainty (K Factor)</b>           | 1,5 m/s <sup>2</sup>              |
| <b>Product Dimensions (L x W x H):</b>            | 282 x 112 x 258 mm                |
| <b>Product net weight (new)</b>                   | 1,4 kg                            |
| <b>System</b>                                     | XGT 40Vmax/80V max                |
| <b>Vibration Level (3 axes)</b>                   | 4,9 m/s <sup>2</sup>              |
| <b>Voltage XGT</b>                                | 1                                 |
| <b>Noise Uncertainty (K Factor)</b>               | 3 dB(A)                           |
| <b>Tool Category</b>                              | Stirring and Compressing          |
| <b>Vibrations per minute</b>                      | 12 000 - 15 500 min <sup>-1</sup> |

### More info

<https://makita.ae/product/concrete-vibrator-xgt-vr001g/>