

## Driver Drill LXT

# DDF486RTJ



### Product Description

18V LXT • 125 Nm • 0 - 2 100 min<sup>-1</sup>

**A powerful, brushless general-use drill for screwdriving and drilling.**

An efficient brushless tool with two speed ranges for screwdriving and drilling for professional use. Max. torque of 130 / 65 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.

### Product Features

- ⦿ Optimum handle design
- ⦿ LED light illuminates the work site
- ⦿ Highly efficient and compact machine for professional use
- ⦿ Battery protection system automatically shuts off power when the battery level is low
- ⦿ Electronic overload protection protects the user and the device

### Barcode

88381739764

### Product Specifications

|  |                        |
|--|------------------------|
| Drilling Capacity Wood (Auger Bit)         | 50 mm                  |
| Vibration Level (3 axes), Drilling         | ≤ 2,5 m/s <sup>2</sup> |
| Torque setting                             | 21                     |
| Drilling Capacity Wood (Self-feed bit)     | 76 mm                  |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion                 |
| Max. Drilling Diameter in Steel            | 13 mm                  |
| Max. Drilling Diameter in Wood             | 76 mm                  |
| Tool weight with battery (EPTA)            | 2,3 - 2,6 kg           |
| Brushless Motor                            | YES                    |
| Battery Voltage                            | 18 V                   |
| Sound Pressure Level                       | 74 dB(A)               |
| Product Dimensions (L x W x H):            | 178 x 81 x 265 mm      |
| Max. fastening torque Hard/Soft            | 130 / 65 Nm            |
| Voltage LXT                                | 1                      |
| Product net weight (new)                   | 1,6 kg                 |
| System                                     | LXT 18V/36V            |
| Driving Shank                              | 1/2"-20UNF "           |
| Vibration Uncertainty (K Factor)           | 1,5 m/s <sup>2</sup>   |

|                              |                                      |
|------------------------------|--------------------------------------|
| Noise Uncertainty (K Factor) | 3 dB(A)                              |
| Drill Chuck Capacity         | 1,5-13 mm                            |
| Tool Category                | Screwing and Drilling                |
| No load speed                | 0 - 550 / 0 - 2100 min <sup>-1</sup> |

Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⦿ Makpac Case

More info

<https://makita.ae/product/driver-drill-lxt-ddf486rtj/>