

Driver Drill LXT DDF486RTJ



Product Description

18V LXT • 125 Nm • 0 - 2 100 min⁻¹

A powerful, brushless general-use drill for screwdriving and drilling.

An efficient brushless tool with two speed ranges for screwdriving and drilling for professional use. Max. torque of 130 / 65 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.

Product Features

- ⊙ Optimum handle design
- ⊙ LED light illuminates the work site
- ⊙ Highly efficient and compact machine for professional use
- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ Electronic overload protection protects the user and the device

Barcode

88381739764

Product Specifications

| | |
|---|------------------------|
| Drilling Capacity Wood (Auger Bit) | 50 mm |
| Vibration Level (3 axes), Drilling | ≤ 2,5 m/s ² |
| Torque setting | 21 |
| Drilling Capacity Wood (Self-feed bit) | 76 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 76 mm |
| Tool weight with battery (EPTA) | 2,3 - 2,6 kg |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Sound Pressure Level | 74 dB(A) |
| Product Dimensions (L x W x H): | 178 x 81 x 265 mm |
| Max. fastening torque Hard/Soft | 130 / 65 Nm |
| Voltage LXT | 1 |
| Product net weight (new) | 1,6 kg |
| System | LXT 18V/36V |
| Driving Shank | 1/2"-20UNF " |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |

| | |
|-------------------------------------|--------------------------------------|
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Drill Chuck Capacity | 1,5-13 mm |
| Tool Category | Screwing and Drilling |
| No load speed | 0 - 550 / 0 - 2100 min ⁻¹ |

Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⦿ Makpac Case

More info

<https://makita.ae/product/driver-drill-lxt-ddf486rtj/>