

Driver Drill LXT

DDF487Z

Product Description

18V LXT • 40 Nm • 0 - 1 700 min⁻¹

A powerful, brushless general-use drill for screwdriving and drilling.

An efficient brushless tool with two speed ranges for screwdriving and drilling for professional use. Max. torque of 40 / 23 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.



Product Features

- ◉ Optimum handle design
- ◉ LED light illuminates the work site
- ◉ Highly efficient and compact machine for professional use
- ◉ Battery protection system automatically shuts off power when the battery level is low
- ◉ Electronic overload protection protects the user and the device

Barcode

88381736558

Product Specifications

| | |
|--|----------------------|
| Drilling Capacity Wood (Auger Bit) | 36 mm |
| Torque setting | 20 |
| Drilling Capacity Wood (Self-feed bit) | 35 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Tool weight with battery (EPTA) | 1,3 - 1,6 kg |
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 36 mm |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Sound Pressure Level | 73 dB(A) |
| Product Dimensions (L x W x H): | 150 x 81 x 248 mm |
| Max. fastening torque Hard/Soft | 40 / 25 Nm |
| Vibration Level (3 axes) | 2,5 m/s ² |

| | |
|---|--------------------------------------|
| Voltage LXT | 1 |
| Product net weight (new) | 0,94 kg |
| System | LXT 18V/36V |
| Driving Shank | 1/2"-20UNF " |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Drill Chuck Capacity | 1,5-13 mm |
| Tool Category | Screwing and Drilling |
| No load speed | 0 - 500 / 0 - 1700 min ⁻¹ |

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/driver-drill-lxt-ddf487z/>