

Driver Drill XGT DF002GA201



Product Description

40V MAX XGT • 64 Nm • 0 - 2 200 min⁻¹

Delivers higher drilling, driving and fastening speed

BL motor delivers 65 N·m (580 in.lbs.) of max torque. Aluminum gear housing creates an impression of rigidity and luxuriousness. 21 clutch settings and drill mode for added fastening control. All metal gear construction for extra-high transmission durability

Product Features

- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Compact and lightweight design
- ⊙ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381735902

Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Torque setting	21
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	38 mm
Tool weight with battery (EPTA)	1,9 - 2,5 kg
Brushless Motor	YES
Battery Voltage	40 V
Sound Pressure Level	78 dB(A)
Product Dimensions (L x W x H):	164 x 86 x 272 mm
Max. fastening torque Hard/Soft	64 / 30 Nm

Product net weight (new)	1,2 kg
System	XGT 40Vmax/80V max
Driving Shank	1/2"-20UNF "
Vibration Uncertainty (K Factor)	1,5 m/s ²
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	750 W
Drill Chuck Capacity	1,5-13 mm
Tool Category	Screwing and Drilling
No load speed	0 - 600 / 0 - 2200 min ⁻¹

Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4020 (2.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

More info

<https://makita.ae/product/driver-drill-xgt-df002ga201/>