

## Driver Drill XGT DF002GZ

### Product Description

40V MAX XGT • 64 Nm • 0 - 2 200 min<sup>-1</sup>

#### Delivers higher drilling, driving and fastening speed

BL motor delivers 65 N·m (580 in.lbs.) of max torque. Aluminum gear housing creates an impression of rigidity and luxuriousness. 21 clutch settings and drill mode for added fastening control. All metal gear construction for extra-high transmission durability



### Product Features

- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Compact and lightweight design
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381735810

### Product Specifications

|  |                        |
|--|------------------------|
| Vibration Level (3 axes), Drilling         | ≤ 2,5 m/s <sup>2</sup> |
| Torque setting                             | 21                     |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion                 |
| Max. Drilling Diameter in Steel            | 13 mm                  |
| Max. Drilling Diameter in Wood             | 38 mm                  |
| Tool weight with battery (EPTA)            | 1,9 - 2,5 kg           |
| Brushless Motor                            | YES                    |
| Battery Voltage                            | 40 V                   |
| Sound Pressure Level                       | 78 dB(A)               |
| Product Dimensions (L x W x H):            | 164 x 86 x 272 mm      |
| Max. fastening torque Hard/Soft            | 64 / 30 Nm             |

|   |                                      |
|---|--------------------------------------|
| <b>Product net weight (new)</b>         | 1,2 kg                               |
| <b>System</b>                           | XGT 40Vmax/80V max                   |
| <b>Driving Shank</b>                    | 1/2"-20UNF "                         |
| <b>Vibration Uncertainty (K Factor)</b> | 1,5 m/s <sup>2</sup>                 |
| <b>Voltage XGT</b>                      | 1                                    |
| <b>Noise Uncertainty (K Factor)</b>     | 3 dB(A)                              |
| <b>Max Output Power</b>                 | 750 W                                |
| <b>Drill Chuck Capacity</b>             | 1,5-13 mm                            |
| <b>Tool Category</b>                    | Screwing and Drilling                |
| <b>No load speed</b>                    | 0 - 600 / 0 - 2200 min <sup>-1</sup> |

#### Standard Equipment

- ⊙ Sold without Battery or Charger

#### More info

<https://makita.ae/product/driver-drill-xgt-df002gz/>