

Electric Breaker XGT HM004GZ01



Product Description

80V • 72.8J • 28.6mm • 870 min⁻¹

This groundbreaking tool is powered by two 40V MAX XGT Li-ion batteries in series, delivering an impressive 80V max high voltage to the hammer.

With the combination of the XGT system and a high-output brushless motor, HM004G offers a remarkable 72.8J impact energy that is equivalent to our corded models. In addition, HM004G achieves an increased work efficiency and a lower vibration level due to its anti vibration housing structure.

HM004G is equipped with numerous features including Constant Speed Control, Soft Start, Soft No Load, Anti-Vibration Technology (AVT), Auto-Start Wireless System (AWS), Extreme Protection Technology (XPT), Maintenance Warning function, Power On/Off function, and Twin LED job lights.

Product Features

- ⊙ Powered by two 40VMAX XGT Lithium-ion batteries to provide 80V MAX volts
- ⊙ High impact energy 72.8J achieved with combination of XGT system with high power brushless motor
- ⊙ Low vibration 6.5m/s² Anti Vibration Housing, Active Dynamic Vibration absorber, Counter Weight Mechanism keeps the vibration lower
- ⊙ Power on/off function prevents accidental startup when the trigger is pressed
- ⊙ Auto power OFF function automatically switches off the power of the hammer, 5 minutes after the trigger switch is released to save battery life and also for operator safety
- ⊙ Low battery Warning indication (blinking RED)
- ⊙ Maintenance Warning Function: When the tool's cumulative operating time exceeds 45 hours, the maintenance indicator lamp blinks red, indicating for maintenance.
- ⊙ Dust Extraction Capability with optional Makita Dust Attachment Kit and also featured AWS technology for wireless power-on/off communication between tool and dust extractor
- ⊙ Soft no load function automatically reduces the speed of the motor when idling to help increase tool life and performance
- ⊙ Constant Speed Control maintain same speed even under load
- ⊙ Soft Start: Breaker starts smoothly then rapidly accelerates to maximum speed to reduce the initial start-up shock
- ⊙ Job Light with TWIN LEDs With preglow and afterglow functions for dark jobsites
- ⊙ eXtreme Protection Technology: Dust and water resistance for operation in harsh conditions
- ⊙ Dust Extractor Attachment Set: 197168-2 (without hose) / 197148-8 (with hose)

Product Specifications

| | |
|---|-------------------------------|
| Impact Energy (EPTA) | 72,8 J |
| Impacts per Minute (IPM) | 870 min ⁻¹ |
| Sound Pressure Level | 95 dB(A) |
| Sound Power Level (LWA) | 103 dB(A) |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Vibration: Chiselling | 6,5 m/s ² |
| Noise Uncertainty (K Factor) | 1.62 dB(A) |
| Brushless Motor | YES |
| AWS FUNCTION | YES |
| Adapted for Hex Shank | 28.6mm |
| Product Dimensions (L x W x H): | 882 x 227 x 540 mm |
| Tool weight without battery (EPTA) | 28.3 kg |
| Battery Voltage | 2 x 40 V MAX |
| System | XGT |
| Tool Category | Hammer Drilling and Chiseling |

Standard Equipment

- Tool Only
- (Sold Without Battery and Charger)

More info

<https://makita.ae/product/electric-breaker-xgt-hm004g01/>