Electric Breaker XGT HM004GZ01

Thakita



Product Description

80V • 72.8J • 28.6mm • 870 min⁻¹

This groundbreaking tool is powered by two 40V MAX XGT Li-ion batteries in series, delivering an impressive 80V max high voltage to the hammer.

With the combination of the XGT system and a high-output brushless motor, HM004G offers a remarkable 72.8J impact energy that is equivalent to our corded models. In addition, HM004G achieves an increased work efficiency and a lower vibration level due to its anti vibration housing structure.

HM004G is equipped with numerous features including Constant Speed Control, Soft Start, Soft No Load, Anti-Vibration Technology (AVT), Auto-Start Wireless System (AWS), Extreme Protection Technology (XPT), Maintenance Warning function, Power On/Off function, and Twin LED job lights.

Product Features

Powered by two 40VMAX XGT Lithium-ion batteries to provide 80V MAX volts

• High impact energy 72.8J achieved with combination of XGT system with high power brushless motor

 \odot Low vibration 6.5m/s² Anti Vibration Housing, Active Dynamic Vibration absorber, Counter Weight Mechanism keeps the vibration lower

Power on/off function prevents accidental startup when the trigger is pressed

 Auto power OFF function automatically switches off the power of the hammer, 5 minutes after the trigger switch is released to save battery life and also for operator safety

Low battery Warning indication (blinking RED)

 Maintenance Warning Function: When the tool's cumulative operating time exceeds 45 hours, the maintenance indicator lamp blinks red, indicating for maintenance.

 Dust Extraction Capability with optional Makita Dust Attachment Kit and also featured AWS technology for wireless power-on/off communication between tool and dust extractor

 \odot Soft no load function automatically reduces the speed of the motor when idling to help increase tool life and performance

Onstant Speed Control maintain same speed even under load

● Soft Start: Breaker starts smoothly then rapidly accelerates to maximum speed to reduce the initial start-up shock

Iob Light with TWIN LEDs With preglow and afterglow functions for dark jobsites

• eXtreme Protection Technology: Dust and water resistance for operation in harsh conditions

• Dust Extractor Attachment Set: 197168-2 (without hose) / 197148-8 (with hose)

Product Specifications	
Impact Energy (EPTA)	72,8 J
Impacts per Minute (IPM)	870 min ⁻¹
Sound Pressure Level	95 dB(A)
Sound Power Level (LWA)	103 dB(A)
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	6,5 m/s ²
Noise Uncertainty (K Factor)	1.62 dB(A)
Brushless Motor	YES
AWS FUNCTION	YES
Adapted for Hex Shank	28.6mm
Product Dimensions (L x W x H):	882 x 227 x 540 mm
Tool weight without battery (EPTA)	28.3 kg
Battery Voltage	2 x 40 V MAX
System	XGT
Tool Category	Hammer Drilling and Chiseling

Standard Equipment

Tool Only

 $\ensuremath{\textcircled{}}$ (Sold Without Battery and Charger)

More info

https://makita.ae/product/electric-breaker-xgt-hm004g01/