

Electric Breaker XGT HM004GZ01



Product Description

80V • 72.8J • 28.6mm • 870 min⁻¹

This groundbreaking tool is powered by two 40V MAX XGT Li-ion batteries in series, delivering an impressive 80V max high voltage to the hammer.

With the combination of the XGT system and a high-output brushless motor, HM004G offers a remarkable 72.8J impact energy that is equivalent to our corded models. In addition, HM004G achieves an increased work efficiency and a lower vibration level due to its anti vibration housing structure.

HM004G is equipped with numerous features including Constant Speed Control, Soft Start, Soft No Load, Anti-Vibration Technology (AVT), Auto-Start Wireless System (AWS), Extreme Protection Technology (XPT), Maintenance Warning function, Power On/Off function, and Twin LED job lights.

Product Features

- ⦿ Powered by two 40VMAX XGT Lithium-ion batteries to provide 80V MAX volts
- ⦿ High impact energy 72.8J achieved with combination of XGT system with high power brushless motor
- ⦿ Low vibration 6.5m/s² Anti Vibration Housing, Active Dynamic Vibration absorber, Counter Weight Mechanism keeps the vibration lower
- ⦿ Power on/off function prevents accidental startup when the trigger is pressed
- ⦿ Auto power OFF function automatically switches off the power of the hammer, 5 minutes after the trigger switch is released to save battery life and also for operator safety
- ⦿ Low battery Warning indication (blinking RED)
- ⦿ Maintenance Warning Function: When the tool's cumulative operating time exceeds 45 hours, the maintenance indicator lamp blinks red, indicating for maintenance.
- ⦿ Dust Extraction Capability with optional Makita Dust Attachment Kit and also featured AWS technology for wireless power-on/off communication between tool and dust extractor
- ⦿ Soft no load function automatically reduces the speed of the motor when idling to help increase tool life and performance
- ⦿ Constant Speed Control maintain same speed even under load
- ⦿ Soft Start: Breaker starts smoothly then rapidly accelerates to maximum speed to reduce the initial start-up shock
- ⦿ Job Light with TWIN LEDs With preglow and afterglow functions for dark jobsites
- ⦿ eXtreme Protection Technology: Dust and water resistance for operation in harsh conditions
- ⦿ Dust Extractor Attachment Set: 197168-2 (without hose) / 197148-8 (with hose)

Product Specifications

Impact Energy (EPTA)	72,8 J
Impacts per Minute (IPM)	870 min ⁻¹
Sound Pressure Level	95 dB(A)
Sound Power Level (LWA)	103 dB(A)
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	6,5 m/s ²
Noise Uncertainty (K Factor)	1.62 dB(A)
Brushless Motor	YES
AWS FUNCTION	YES
Adapted for Hex Shank	28.6mm
Product Dimensions (L x W x H):	882 x 227 x 540 mm
Tool weight without battery (EPTA)	28.3 kg
Battery Voltage	2 x 40 V MAX
System	XGT
Tool Category	Hammer Drilling and Chiseling

Standard Equipment

- Tool Only
- (Sold Without Battery and Charger)

More info

<https://makita.ae/product/electric-breaker-xgt-hm004g01/>