



Finishing Sander LXT DBO482Z



Product Description

18V LXT • 114 x 140 mm

Cordless Finishing Sander LXT® for various sanding operations.

DBO482 has 14 000 OPM for fast and smooth finish sanding. Electric brake for increased productivity. DBO482 can be equipped with various sanding pads. Large clamping lever for quick and easy paper installation.

Product Specifications

Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Sanding Pad Dimensions	112-102 mm
Sanding Orbit Diameter	1,5 mm
Tool weight with battery (EPTA)	1,4 - 1,8 kg
Battery Voltage	18 V
Dimensions of Clamped Abrasive Sheet	114-140 mm
Pad size (triangle)	96 x 96 mm
Sound Pressure Level	75 dB(A)
Product Dimensions (L x W x H):	171 x 112 x 150 mm
Strokes per Minute (SPM)	22000 / 28000 min ⁻¹
Max Output Power	210 W
Orbits per Minute	0-14000 min ⁻¹
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration Level (3 axes)	3,4 m/s ²
Voltage LXT	1
Product net weight (new)	1,1 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	3 dB(A)
Vacuum cleaner connection Ø in / out	17/22 mm
Vibrations per minute	11000 / 14000 min ⁻¹
Tool Category	Grinding, Sanding and Polishing

Standard Equipment

◎ Sold without Battery or Charger

More info

<https://makita.ae/product/finishing-sander-lxt-dbo482z/>