

Flat-Head Angle Grinder XGT GA056GZ



Product Description

40V MAX XGT • 125mm • Paddle Switch • BL Motor • AFT • XPT
Cordless Flat-Head Angle Grinder powered by 40Vmax XGT Li-Ion battery.

Features a Paddle Switch. Reduced access angle at the tip enables excellent workability for deburring in confined or recessed areas. Equipped with a newly designed tool-less wheel cover for flat head angle grinders, allowing access at angles as small as 39°.

Product Features

- ⊙ 40Vmax XGT Cordless 125 mm (5") Flat-Head Angle Grinder
- ⊙ Reduced access angle at the tip enables excellent workability for deburring in confined or recessed areas
- ⊙ Equipped with a newly designed tool-less wheel cover for flat-head angle grinders, allowing access at angles as small as 39°
- ⊙ High work efficiency has been achieved by using high voltage 40Vmax XGT Li-Ion battery and BL motor
- ⊙ Active Feedback sensing Technology (AFT) turns the motor off if rotation speed suddenly slows or wheel is forced to stop
- ⊙ Electric brake for maximum productivity
- ⊙ Paddle switch; Easy-to-hold slim grip achieved by optimized parts allocation
- ⊙ Anti-restart function engineered to minimize motor start up when battery is inserted with switch locked on
- ⊙ Extreme Protection Technology (XPT)

Product Specifications

Wheel Diameter	
Minimum Access Angle	
No Load Speed	
Cutting Depth	
Dimensions (LxWxH)	
Net Weight	
Wheel Diameter	125 mm (5")
Minimum Access Angle	39 °
No Load Speed	3,000 - 9,000 min-1
Cutting Depth	30 mm
Dimensions (LxWxH)	483 x 140 x 136 mm (with BL4040F)
Net Weight	2.5 kg (without battery)

Standard Equipment

- ⦿ Side Grip
- ⦿ Adapter
- ⦿ Lock Nut Wrench
- ⦿ Wheel Cover for cut-off Wheel

More info

<https://makita.ae/product/flat-head-angle-grinder-xgt-ga056gz/>