



## Hammer Drill Driver LXT DHP453RFE



### Product Description

18V LXT • 42 Nm • 0 - 1 300 min<sup>-1</sup>

#### Combi drill with hammer action for demanding amateur builders

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use. Includes 2 x 3,0 Ah batteries and a charger in a case.

### Product Features

- ◎ The rubber coating on the handle ensures a firm working grip
- ◎ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381661249

### Product Specifications

<b>Vibration Level (3 axes), Drilling</b>	≤ 2,5 m/s <sup>2</sup>
<b>Torque setting</b>	16
<b>Max. Drilling Diameter in Steel</b>	13 mm
<b>Max. Drilling Diameter in Wood</b>	36 mm
<b>Vibration Level (3 axes), Impact Drilling</b>	10,0 m/s <sup>2</sup>
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Tool weight with battery (EPTA)</b>	1,7 - 2,0 kg
<b>Battery Voltage</b>	18 V
<b>Sound Pressure Level</b>	83 dB(A)
<b>Product Dimensions (L x W x H):</b>	239 x 79 x 227 mm
<b>Max. fastening torque Hard/Soft</b>	42 / 27 Nm
<b>Impacts per Minute (IPM)</b>	0 - 6000 / 19500 min <sup>-1</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	94 dB(A)
<b>Voltage LXT</b>	1
<b>Product net weight (new)</b>	1,4 kg
<b>System</b>	LXT 18V/36V
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Driving Shank</b>	1/2"-20UNF "
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Screwing and Drilling
<b>Drill Chuck Capacity</b>	1,5-13 mm
<b>Electronic brake</b>	1

<b>Max. Drilling Diameter in Concrete</b>	13 mm
<b>Max. Drilling Diameter in Masonry</b>	13 mm
<b>No load speed</b>	0 - 400 / 1300 min <sup>-1</sup>

### Standard Equipment

- ◎ 1pc DC18RC Fast Charger
- ◎ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ◎ Carry Case

### More info

<https://makita.ae/product/hammer-drill-driver-lxt-dhp453rfe/>