

## **Impact Drill**

# **HP1640K**



#### **Product Description**

680 W • 16 mm • 0 - 2 800 min<sup>-1</sup>

### Compact drill with hammer and drive functions

Compact 680 W percussion drill with a masonry drilling capacity of 16 mm. A slimline frame and large switch for added usability. With rugged aluminium housing for gear drive. 13 mm quick action drill chuck. Comes in a case.

#### **Product Features**

- Drill with drilling and impact drilling
- Rubberized soft grip for more comfort and control
- Same speed and torque in both directions with reverse gear.
- Variable speed control dial enables user to match the speed to the application
- Double insulated

Product Specifications	
Plastic Carrying Case	1
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	30 mm
Vibration Level (3 axes), Impact Drilling	19 m/s <sup>2</sup>
Sound Pressure Level	92 dB(A)
Power Supply Cord	2,0 m
Continuous Input Power	680 W
Vibration Uncertainty (K Factor)	2,0 m/s <sup>2</sup>
Product Dimensions (L x W x H):	303 x 72 x 222 mm
Impacts per Minute (IPM)	0 - 44800 min <sup>-1</sup>
Vibration Level (3 axes)	≤ 2,5 m/s²
Sound Power Level (L <sub>WA</sub> )	103 dB(A)
Weight Without Cable (EPTA)	2,0 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Concrete	16 mm
Drill Chuck Capacity	1,5-13 mm
Tool Category	Screwing and Drilling
No load speed	0 - 2800 min <sup>-1</sup>
Collar Clamping Diameter	43 mm

#### More info