

Impact Drill

HP1640KX3



Product Description

680 W • 16 mm • 0 - 2 800 min⁻¹

Compact drill with hammer and drive functions

Compact 680 W percussion drill with a masonry drilling capacity of 16 mm. A slimline frame and large switch for added usability. With rugged aluminium housing for gear drive. 13 mm quick action drill chuck. 74pcs Driver Set in a case.

Product Features

- ⦿ Drill with drilling and impact drilling
- ⦿ Rubberized soft grip for more comfort and control
- ⦿ Same speed and torque in both directions with reverse gear.
- ⦿ Variable speed control dial enables user to match the speed to the application
- ⦿ Double insulated

Product Specifications

Plastic Carrying Case	1
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	30 mm
Vibration Level (3 axes), Impact Drilling	19 m/s ²
Sound Pressure Level	92 dB(A)
Power Supply Cord	2,0 m
Continuous Input Power	680 W
Vibration Uncertainty (K Factor)	2,0 m/s ²
Product Dimensions (L x W x H):	303 x 72 x 222 mm
Impacts per Minute (IPM)	0 - 44800 min ⁻¹
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L _{WA})	103 dB(A)
Weight Without Cable (EPTA)	2,0 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Concrete	16 mm
Drill Chuck Capacity	1,5-13 mm
Tool Category	Screwing and Drilling
No load speed	0 - 2800 min ⁻¹
Collar Clamping Diameter	43 mm

More info

<https://makita.ae/product/impact-drill-hp1640kx3/>