

Impact Drill

HP2050



Product Description

720 W • 20 mm • 0 - 2 900 min⁻¹

Efficient drill with hammer and drive functions and two power settings

An efficient, 720 W percussion drill with two power settings. Masonry drilling capacity of 20 mm. With rugged aluminium housing for gear drive and safety clutch for stopping the motor if the drill bit gets stuck. 13 mm full-metal guick action drill chuck.

Product Features

- 2-mode operation for "Rotation Only" or "Hammering with Rotation"
- Variable speed control enables user to match the speed to the application
- Rubberized soft grip for more comfort and control
- Double insulated

Barcode

88381043212

Product Specifications	
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	40 mm
Vibration Level (3 axes), Impact Drilling	13 m/s²
Sound Pressure Level	97 dB(A)
Power Supply Cord	2,5 m
Continuous Input Power	720 W
Vibration Uncertainty (K Factor)	3,0 m/s ²
Product Dimensions (L x W x H):	360 x 70 x 220 mm
Impacts per Minute (IPM)	0 - 24000 / 58000 min ⁻¹
Vibration Level (3 axes)	≤ 2,5 m/s²
Sound Power Level (L _{WA})	108 dB(A)
Weight Without Cable (EPTA)	2,5 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Masonry	20 mm
Drill Chuck Capacity	1,5-13 mm
Tool Category	Screwing and Drilling
No load speed	0 - 1200 / 0 - 2900 min ⁻¹
Collar Clamping Diameter	43 mm

More info