

## Impact Drill HP2050



### Product Description

720 W • 20 mm • 0 - 2 900 min<sup>-1</sup>

#### Efficient drill with hammer and drive functions and two power settings

An efficient, 720 W percussion drill with two power settings. Masonry drilling capacity of 20 mm. With rugged aluminium housing for gear drive and safety clutch for stopping the motor if the drill bit gets stuck. 13 mm full-metal quick action drill chuck.

### Product Features

- ⊙ 2-mode operation for "Rotation Only" or "Hammering with Rotation"
- ⊙ Variable speed control enables user to match the speed to the application
- ⊙ Rubberized soft grip for more comfort and control
- ⊙ Double insulated

### Barcode

88381043212

### Product Specifications

|   |                                       |
|---|---------------------------------------|
| Max. Drilling Diameter in Steel           | 13 mm                                 |
| Max. Drilling Diameter in Wood            | 40 mm                                 |
| Vibration Level (3 axes), Impact Drilling | 13 m/s <sup>2</sup>                   |
| Sound Pressure Level                      | 97 dB(A)                              |
| Power Supply Cord                         | 2,5 m                                 |
| Continuous Input Power                    | 720 W                                 |
| Vibration Uncertainty (K Factor)          | 3,0 m/s <sup>2</sup>                  |
| Product Dimensions (L x W x H):           | 360 x 70 x 220 mm                     |
| Impacts per Minute (IPM)                  | 0 - 24000 / 58000 min <sup>-1</sup>   |
| Vibration Level (3 axes)                  | ≤ 2,5 m/s <sup>2</sup>                |
| Sound Power Level (L <sub>WA</sub> )      | 108 dB(A)                             |
| Weight Without Cable (EPTA)               | 2,5 kg                                |
| Noise Uncertainty (K Factor)              | 3 dB(A)                               |
| Max. Drilling Diameter in Concrete        | 20 mm                                 |
| Max. Drilling Diameter in Masonry         | 20 mm                                 |
| Drill Chuck Capacity                      | 1,5-13 mm                             |
| Tool Category                             | Screwing and Drilling                 |
| No load speed                             | 0 - 1200 / 0 - 2900 min <sup>-1</sup> |
| Collar Clamping Diameter                  | 43 mm                                 |

### More info

<https://makita.ae/product/impact-drill-hp2050/>