

Impact Driver

6953



Product Description

280 W • 1/2" • 150 Nm • 0 - 3 000 min⁻¹

Compact impact driver for quick driving

A compact and light impact driver with a hex. 1/2" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 150 Nm, suitable for quick driving. Comes in a case.

Product Specifications

Drive Square	1/2" "
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	233 x 67 x 180 mm
Tightening Capacity High Tensile Bolt	M8 - M12
Vibration Uncertainty (K Factor)	1,5 m/s ²
Continuous Input Power	280 W
Sound Pressure Level	99 dB(A)
Vibration Level (3 axes), Fastening Bolt	8,5 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)
Tightening Capacity Standard Bolt	M10 - M16
Weight Without Cable (EPTA)	1,5 kg
Tool Category	Screwing and Drilling
No load speed	0 - 3000 / 0 - 1300 min ⁻¹
Impacts per Minute (IPM)	3000 min ⁻¹
Max Fastening Torque Impact Drill	150 Nm
Sound Power Level (L _{WA})	107 dB(A)
Product net weight (new)	1,4 kg

More info

<https://makita.ae/product/impact-driver-6953/>