



Impact Driver 7.2V TD022DSJ



Product Description

7.2V • 1/4" • 25 Nm • 0 - 2 450 min-1

Compact, high-speed impact driver

A compact, 7.2V pencil impact driver. An ideal tool for tight, awkward spaces, equipped with an LED light. Torque of 25 Nm. Two 1.5Ah batteries and a charger in a Makpac case.

Product Features

- LED light illuminates the work site

Barcode

88381833288

Product Specifications

Tool weight with battery (EPTA)	0,55 - 0,56 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	7,2 V
Vibration Level (3 axes), Fastening Bolt	7,0 m/s ²
Sound Pressure Level	85 dB(A)
Capacity machine screw	M3 - M8
Vibration Uncertainty (K Factor)	1,5 m/s ²
Driving Shank	0.25 "
Tightening Capacity High Tensile Bolt	M3 - M6
Product Dimensions (L x W x H):	282 x 42 x 52 mm
Product net weight (new)	0,45 kg
Impacts per Minute (IPM)	0 - 3000 min ⁻¹
Sound Power Level (L_{WA})	96 dB(A)
Max Fastening Torque Impact Drill	25 Nm
Tightening Capacity Standard Bolt	M3 - M8
Dimensions, foldable (L x W x H)	227 x 42 x 142 mm
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
No load speed	0 - 2450 min ⁻¹

Standard Equipment

- 2pcs 7.2V (1.5Ah) Battery
- 1pc Charger

More info

<https://makita.ae/product/impact-driver-7-2v-td022dsj/>