

Impact Driver LXT

DTD153Z



Product Description

18V LXT • 1/4" • 170 Nm • 0 - 3 400 min⁻¹

Extra-compact brushless impact driver for quick drivingA compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 170 Nm, suitable for quick driving. A handy LED light for added lighting. Tool only, battery and charger not included.

Product Features

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site

Barcode

88381823883

Product Specifications

| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
|--|----------------------------|
| | |
| Tool weight with battery (EPTA) | 1,3 - 1,6 kg |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Vibration Level (3 axes), Fastening Bolt | 13,0 m/s ² |
| Sound Pressure Level | 96 dB(A) |
| Capacity machine screw | M4 - M8 |
| Product Dimensions (L x W x H): | 126 x 79 x 238 mm |
| Tightening Capacity High Tensile Bolt | M5 - M14 |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Driving Shank | 0.25 " |
| Sound Power Level (L _{wA}) | 107 dB(A) |
| Impacts per Minute (IPM) | 0 - 3600 min ⁻¹ |

| Max Fastening Torque Impact Drill | 170 Nm |
|-----------------------------------|----------------------------|
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 0,90 kg |
| Tightening Capacity Standard Bolt | M5 - M16 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Tool Category | Screwing and Drilling |
| No load speed | 0 - 3400 min ⁻¹ |

Standard Equipment

Sold without Battery or Charger

More info

https://makita.ae/product/impact-driver-lxt-dtd153z/